

## SETUP SHEET



TRACK CONDITIONS								
Size:	low	1	<u>2</u>	3	4	5	high	Track Temp/Air Temp: <u>    </u> ° / <u>    </u> °
Traction:	low	1	2	<u>3</u>	4	5	high	Best Lap: <u>                    </u>
								Note: <u>                                    </u>

### FRONT

Stabilizer Length     

Camber Angle -1 °

Castor 3 °

Ride Height 5 mm

Down Stop 4 mm

Front Drive Diff One-Way Spool

Stabilizer 1.1 1.2 1.3 1.4 1.5 mm

Stabilizer Length      mm

Notes                                     

F      mm R      mm

### SHOCKS

	Front	Rear
Piston	Hole Size <u>1.2</u> mm	Hole Size <u>1.2</u> mm
	# of Holes <u>1 2 3</u>	# of Holes <u>1 2 3</u>
Oil wt.	<u>30</u>	<u>30</u>
Oil Brand	<u>TM</u>	<u>TM</u>
Springs	<u>Kit gold</u>	<u>Kit gold</u>
Oring	<u>    </u>	<u>    </u>
Bladder note	<u>    </u>	<u>    </u>
Front	<u>    </u> mm	<u>    </u> mm
Rear	<u>    </u> mm	<u>    </u> mm

Thread Length     

### REAR

Stabilizer Length     

Camber Angle -2 °

Ride Height 5 mm

Down Stop -2 mm

Stabilizer 1.1 1.2 1.3 1.4 1.5 mm

Stabilizer Length      mm

Shim      mm

Rear Wheelbase      °

Notes                                     

F      mm R      mm

### TIRES

	Front	Rear
Brand	<u>RP 30</u>	<u>RP 30</u>
Compound	<u>    </u>	<u>    </u>
Insert	<u>    </u>	<u>    </u>
Wheel	<u>    </u>	<u>    </u>
Traction Compound	<u>NOSRAM Inside edge</u>	<u>NOSRAM</u>
Notes	<u>    </u>	<u>    </u>

F Toe Angle 2 ° R Toe Angle 2-5 °

Spur & Pinion

Spur (S) 109

Pinion (P) 28

$\frac{S}{P} = 3.89 \times 2.0588 = R$

Final Drive Ratio (R) 8-01

Body DNA 2

Wing DNA 2

### Wheel Hubs

F Widthspacer 0 mm

R Widthspacer 2 mm

Front Width 185 mm

Rear Width 189 mm

R Upright spacer      mm

Front 0.9 mm Rear 0.9 mm

### Electronics

Transmitter Futaba

Receiver Spektrum

Servo Bluebird

ESC MRT

Battery EP 4200

### Motor

Brand Checkpoint

Turns 19

Brushes infinity silver

Springs Checkpoint hard

Timing